

UV2 Series

Emergency Return/Battery Backup System



PREVENT ELEVATOR ENTRAPMENT

Automatically activates during a power failure, moving the car to an available floor and opening the doors to free passengers

Features & Operation:

- Powers controller & maintains safety circuits
- Built-in dry contacts & switched 24VDC
- Compact, wall mounted steel cabinet
- On-board battery charging system
- Single-phase AC &/or DC power

Safety, Troubleshooting & Maintenance:

- Primary side installation available
- Fused batteries, outputs, logic & battery charger circuitry
- Single board design



UNIT CHARACTERISTICS

- Voltage Options: 120, 208, 240 or 480 VAC (1Ø, 60 Hz) w/optional 260 VDC door power
- Power: 500VA Continuous, 750VA Peak
- Dimensions: 12.5"H x 12.5"W x 8"D
- Approx. Weight: 35lbs w/o batteries; 55lbs w/batteries

Designed for Hydraulic Elevator Systems



Technical Support

Reynolds & Reynolds Electronics, Inc. (R&R) offers complimentary technical support before, during and after installation for all of our products.



Made in the USA since 1989

R&R is a leading manufacturer of Emergency Return Systems/ Battery Backup for traction and hydraulic passenger/freight elevators, Emergency Brake Release Units and Elevator Door Controllers.

CONTACT

reynoldselectronics.com



2501 Baglyos Circle in Bethlehem, PA 18020



(610) 691-2224



admin@reynoldselectronics.com